

HD-IP IR PTZ MEDIUM SPEED DOME



PTZ Camera for Long Distance

ARN-HD611-20X

- * Support P2P function, H.265
- * 1/2.8" SONY Starvis Back-illuminated CMOS sensor GK7205V300+SONY335
- * 5MP, 18X Zoom f=4.7mm~96.3mm
- * 4.5" Half Metal Body Construction, IP66
- * ONVIF ; Compatible
- * Intelligent IR illumination & power consumption is variable, dependent the zoom factor

Specification

Camera	
Resolution	5MP 2560*1920
Chipset+Sensor	GK7205V300+SONY335
Lens	10X f=5.1~51mm 18X f=4.7mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, EasyVMS, P2P(P6SLite)
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Rotation Speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmabel(scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
Operating temperature	-40°~+60°C
Operation menu	English
Power	DC 12V
Consumption	≤15W
Related validation	IP66
IR distance	Up to 80 meters
LEDs	Yes