

5MP Bullet IP Camera



ARN – B35-5X

 **Area Detection**

 **Target Count**

 **Object Left/Lost**

 **Line Crossing**

Features

1. 1/2.8" 5.0 Megapixels Progressive Scan Sony CMOS
2. Max 1-20 Megapixels 1-25 fps @4.0 Megapixels/2.0 Megapixels
3. Privacy Mask, Motion Detection
4. H.264 /H.265 & MJPEG dual-stream encoding 5. Multiple network monitoring: Web viewer, Smart phone.
5. 5MP 2.7-13.5MM 5X Motorized lens, 24pcs LEDs, up to 40M IR distance

Technical parameters

Model:	ARN – B35-5X
Camera	
Media Processor	Hi3516D+Sony imx335
Image Sensor	1/2.8" 5.0 megapixels Progressive Sony imx335 CMOS
Effective Pixels	2592(H)x1944(V)
Shuttle time	Auto (1/25 ~ 1/10000s)
Min. Illumination	0.01Lux/F1.2(Color) 0Lux/F1.2(B/W)
Lens Specifications	5MP 2.7-13.5MM 5X Motorized lens
Day/Night Mode	Auto (ICR)/Color/B/W
IR Distance	24PCS LEDs, up to 40M IR distance
S/N Ratio	≥50db(AGC OFF)
White Balance	Auto
Gain Control	Auto
WDR	Digital WDR ≥80db
Image	
Compression	H.264 /H.265/MJPEG
Max Image Size	1920(H)x1944(V)
Stream	Dual-stream
Frame Rate	Main Stream : 5MP,1-20fps ; 4MP/2MP,1-25fps
Bit Rate	32KB ~16Mbps; support VBR; CBR
Text Overlay	Channel; Date & Time; Bit Rate
Network	
Data Storage	Video record; Picture format
Trigger	Manual; Automatic (motion detection; alarm; schedule; cycle)
Alarm data transmission	FTP; E-mail; Browser; CMS

146 Brookline Ave, 7th Floor, Boston, MA 02215, USA

18A, Unit2, Bid 5, HaojingCheng, HaoYi Shajing, Bao'an District, Shenzhen City, Guangdong, China

Phone: +8613554983743 Web: www.airnet-technology.com

Technical parameters

Protocol	TCP/IP/IUDP/IRTP/IRTSP/IRTCP/IHTTP/IDNS/IDDNS/IDHCP/IFTP/INTP/IPPPOE/ISMTTP/IUPNP
ONVIF	ONVIF 2.4
Max. User Access	10 users; IE; Google; Firefox
Smart Phone	Windows Mobile; iPhone; iPad; Android
Interface	
Audio IN	Support
Audio OUT	Support
BNC Video OUT	N/A
Memory Card	N/A
RS422/RS485	N/A
USB	Support (64G USB flash/WIFI/3G)
Alarm IN	N/A
Alarm OUT	N/A
IO Interface	Support (Reset)
General	
Power Supply	DC12V/POE
Operation Temperature	-20°C - +50°C
Operation Humidity	Less than 95% RH (no condensation)
Weather Proof Rating	IP66
Dimension	270X120X120MM
Weight	1Kg