

2MP Bullet IP Camera**Feature****ARN-36I9-2MP**

- ❖ Structure: Embedded RTOS,HI3516EV200
- ❖ Sensor: 2 mega pixel 1/2.8" CMOS SENSOR (IMX307)
- ❖ Video: H265+/H265 /H.264 compression, Dual Streaming
- ❖ Resolution: Main Stream:1920*1080(2mp),1280*720
Sub-stream:448P,VGA,640*360, CIF
- ❖ Frame Rate: 1920*1080 30fps,Support 7~30fps adjustable
- ❖ Network port: 10/100M self-adapt Ethernet port,6KV anti-static.
- ❖ Support HTTP/RTSP/DHCP/NTP/ONVIF/P2P,etc;
- ❖ Optional Function: POE, audio

PARAMETERS

Specification	ARN-36I9-2MP
Structure	Hisilicon HI3516E V200+ 1/2.8" CMOS IMX307
Minimum Illumination	Color 0.01 Lux @ F1.2, Black-white 0.001 Lux @ F1.2
SNR	≥ 50 dB
AUDIO	Optional G.711(Default not included)
Privacy mask	Support 4ch Privacy masking area
VIDEO	Support OSD,BLC,HLC,DWDR, 3DNR; Brightness/Contrast/Saturation/Sharpness Adjustable Support Motion Detection Alarm Recording
lens	2mp 3.6mm, Optional 6mm/8mm/12mm
IR Led	36pcs IR Led, IR distance 25-35m
frequency	50Hz/60Hz
Video Coded Format	H.264 /H265/H265+
Image Resolution	Main Stream: 1920*1080,1-30fps; 1280*720, 1-30fps; Sub-stream: 448P,VGA,640*360, CIF, 1-30fps
Video Compression Rate	500Kbps-8Mbps continuously adjustable, support CBR/VBR
Network Port	10/100M self-adapt Ethernet port, lightning protection
Protocol	Support HTTP/RTSP/DHCP/NTP/ONVIF/P2P,etc;
Phone Client	Support iPhone, Android
browser	Support IE6.0 and above (equipment embedded Web Server) browser,
Business Function	Support unit client software, support CMS platform system application
Feature	Support day/night (support IR-CUT) , support LDR signal linkage
General Parameters	DC12V, 5W Max
Device Size	165 * 62 *62mm
Package Size	200*110*100mm